



Global System Technology PLC

The Intelligent Solution

# Handheld Programmer P-9910



### **Technical Specification**

- Single point programming and interrogation of GST I-9000 Series detectors and protocol
- Power supply: one 9V batteryWorking current: ≤8mA
- Standby current: ≤50µA
- Operating environment:Temperature: -20oC+70
- Relative humidity: ≤95 % 40±2°C
- Physical dimensions: 164mm×64mm×24mm



#### **Feature**

- Portable programming tool for addressing and testing of intelligent devices
- Digital programming
- Programs all loop devices (1-242 addresses per loop)
- Non-polarized 2 wire intelligent programmer
- Interrogates devices for conditions
- Reprogram facility enables adjustment to alarm sensitivity of detectors
- Adjust inputs modules to accept N/C or N/O contacts
- Low power consumption with sleep and auto off mode.
- Battery low indication
- Display type: Four-bit LCD
- Easy operation Hand held engineering tool.

# Selection of compatible

Compatible with all GST Intelligent devices

#### Ordering Information:

Part No	Description	Pack Qty per Box
P-9910	Handheld Programmer	1



www.gst.uk.com info@gst.uk.com

## Description

The P-9910 GST protocol programming tool, capable of reading and writing address codes, displaying model number, year of manufacture and batch number, plus display and adjust analogue sensitivity. Enable to adjust alarm threshold, N/C or N/O and switch on or off the rate of rise of dual heat detector.

MANUFACTURED IN ACCORDANCE WITH



Note: Specifications are subject to change without notice.

**GST England** 

Lion Court, Staunton Harold Hall, Melbourne Road, Ashby de la Zouch, Leicestershire, England LE65 1RT Tel: +44 1283 225 478 Fax: +44 1283 220 690

GST Dubai

ZA04, Jebel Ali Free Zone, P.O.Box 17998, Dubai UAE Tel: +971 (0)4 8833 050 Fax: +971 (0)4 8833 053

GST China

80, Changjiang East Road, Economic & Technology Development Zone Qinhuangdao, Hebei, China Tel: +86(0)335 850 2383 Fax: +86 (0)335 850 7588